



ITONA TI 5521

Networking Ideas
..... Thin Solutions

Thin Client



Itona TI is available with a variety of operating systems (Gio Linux, Mozilla, Microsoft Windows CE and Microsoft Windows XP Embedded) so it connects easily to a wide range of servers and networks. With integrated 54Mbps wireless LAN as well as a 56K/V.92 modem and 10/100 Ethernet, Itona TI delivers the security and central manageability of thin client computing – in a package.

Itona TI gives you all the advantages of thin client computing with integrated LCD Panel.



About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide – with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters is in Bangalore, India.

Fully featured

With an extensive range of ports (USB x4, PS/2 x2, audio, headphone, 10/100 Ethernet, wireless LAN, VGA out and parallel port), 32-bit graphics display and Itona TI has got pretty much everything you need. If you want more, you'll be pleased to hear that RAM can be upgraded to 1Gb – and Flash memory to 1Gb.

Secure mobile computing

Central data storage, remote management software and workstation-class security – in a device.

Choice. Choice. And choice.

Itona comes in a range of configurations, so you can be sure that there's an ideal Itona for your network.

Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

ITONA TI 5521

Thin Client



Modular Terminal

Based on the Microsoft Windows XP Embedded operating system
Standard Client Software:

Citrix ICA, Integrated Microsoft RDP, Internet Explorer, terminal emulation protocols standard.
Standard with 256MB Flash & 256MB SDRAM

Hardware

Processor : VIA C3 1000 MHz

Input/Output/Peripheral Support :

- 2 serial port
- 2 USB 2.0 ports
- PS/2 Keyboard
- PS/2 Mouse
- VGA video output (DB-15)
- Dual Channel LVDS interface
- 1 Parallel Port (Female Connector D-Sub 25P)
- Internal slim HDD (Optional)

Monitor (In-built LCD Display Panel)

- 17" LCD Display with Touch Panel
- 1280X1024 resolution
- Pixel Pitch 0.264x 0.264(mm²)
- Luminance 260 cd/m²
- Dual Channel LVDS interface
- ELO 5-Wire resistive (Optional)
- USB Interface
- Point density 4096x4096

Networking

- Autosensing, 10/100 Ethernet, RJ-45
- 802.11b+g WLAN : External Antenna
- Wake On Lan
- PXE boot

Display Support

- Maximum resolution Up to 1280x1024
- Support two displays dual view
- Extended video support

Audio

- Line Out
- Mic

OPTIONS

- 1 x 2.5" HDD
- Smart Card Reader
- PCMCIA Slot

Physical Characteristics

- Unit: 42.5cm x 39 cm x 21 cm (vertical)
- Packing: 27cm x 56 cm x 50.5 cm

Ambient Temperature Range

- Temperature Range : Powered on: 32° to 104°F (0° to 40°C)
- Humidity : 20% to 80% noncondensing

Software

Firmware Features :

- Microsoft Windows XPE
- Microsoft Internet Explorer 6.0 resident: 1 HTML, JavaScript, XML, Active X, Sun JRE, MediaPlayer 6.4
- Media Player Ver 9.0
- RDP 5.2 resident
- Citrix ICA 9.0 resident
- Terminal emulation emulates 60 terminal types

Server OS Compatibility/Support :

- Microsoft Windows 2000/2003 Server
- Citrix Winframe and MetaFrame SECURITY :
- EWF Manager, User registry restrictions
- Microsoft Windows NT Server 4.0 Terminal Server Edition
- PLUG-INS :
- Adobe Acrobat Reader, Macromedia Flash wave and Shock wave

Set-Up and Configuration :

User interface :

- Boot from local Flash
- Windows XP user interface language: U.S. English; French, German, Spanish optional
- Keyboard language support: U.S. English standard; All other languages supported
- JAVA/JVM, VNC Shadowing
- PPP / DIAL-UP- Networking
- VPN, Customizable Thinprint
- USB Input Devices Support
- Smart Card Support, ELO Touch screen Support
- My ODBC Client Support

Protocol Support :

- TCP/IP, DNS, DHCP, PXE, PPP

Management

- Remote management, configuration, and upgrades through XLmanage software version 1.2 or later
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration (IP information, name, etc.)
- Reporting
- Remote screen shadowing of entire desktop (VNC)
- Asset management

Power

- External power Adapter 12 Volt 80 Watt.
- Worldwide auto-sensing 100-240 VAC., 50/60 Hz

Regulatory Compliance

- UL & CE

Warranty

One-year limited warranty



VXL Instruments Limited

Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines)

Fax: +91 80 28520095

E-mail: sales@vxl.net

Web: www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55

Fax: +44 (0) 16 17 75 48 66

E-mail: peter.best@vxl.net

VXL Presence:

France

Tel. : +33 (0) 1 42 17 00 03

E-mail: pjaspard@vxl.net

Germany

Tel. : +49 (0) 8761 1093

E-mail: gerdb@vxl.net

United States

Tel. : +1 713 589 3273

E-mail: sales@vxl.net