



ITONA TL 3721

Networking Ideas
..... Thin Solutions

Thin Client



Itona TL is available with a variety of operating systems (Gio Linux and Microsoft Windows XP Embedded) so it connects easily to a wide range of servers and networks. With integrated 54Mbps wireless LAN as well as a 56K/V.92 modem and 10/100/1000 Ethernet, Itona TL delivers the security and central manageability of thin client computing - in a package that's as portable as it is stylish.

Itona TL gives you all the advantages of thin client computing - in a light, powerful laptop. Thin client computing, to go.



Itona TL

About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide - with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters is in Bangalore, India.

Fully featured

With an extensive range of ports (USB x3, audio, headphone, 10/100/1000 Ethernet, wireless LAN, VGA out and optional PCMCIA support), 32-bit graphics display and a removable battery, Itona TL has got pretty much everything you need. If you want more, you'll be pleased to hear that RAM can be upgraded to 2 GB - and Flash memory to 1 GB.

Secure mobile computing

Central data storage, remote management software, BIOS password protection and a Kensington lock deliver workstation-class security - in a mobile device.

Choice. Choice. And choice.

Itona comes in a range of configurations, so you can be sure that there's an ideal Itona for your network.

Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

ITONA TL 3721

Thin Client



Modular Terminal

Based on Microsoft XP : SP2

Standard Client Software:

256MB (ATA Flash Drive 2.5") 256 MB SO-DIMM DDR333/400MHz, Memory Expandable upto 1GB

Hardware

Processor : VIA C7-M Processor 754 (1.50GHz)

Input/Output/Peripheral Support :

- 3 USB 2.0 ports
- 1x External CRT monitor output
- 1x Headphone jack
- 1x Microphone jack
- 1x S/PDIF output jack
- 1x RJ-45 port for LAN
- 1x RJ-11 port for Modem (functional option)
- 1x Line-in jack
- 1x DC-In jack
- A4 size keyboard, Multi-Language support, Winkey Keyboard
- Built-in Touchpad with scrolling function
- One Type-II PCMCIA CardBus PC Card Slot.
- Embedded 4 in 1 Card Reader.
- Optional PCMCIA support

Networking

- 10/100BASE-TX Fast Ethernet on board
- (Option) 802.11g MiniPCI Wireless LAN

Display Support

- 15" XGA + TFT
- High resolution 1024 x 768 with 32 bit
- Dual monitor display support
- Dual monitor extended video support

Audio

- AC'97 2.2 Compliant Interface
- 3D stereo enhanced sound system
- Virtual 6-channel audio output
- Sound-Blaster PROTM Compatible
- S/PDIF Digital output (5.1 CH)
- 1x Built-in Microphone
- 2x Built-in Speakers

Physical Characteristics

- Height : 1.3 Inches (33mm.)
- Depth : 10.9 inches (276mm)
- Desktop type Only
- Width : 13.1 inches (325mm)
- Shipping Weight : 2.5Kg with 6 cells

Temperature Range :

- 5 dec - 35 dec

Security :

- Security (Kensington R Type) Lock Slot, BIOS Password

Software

Firmware Features :

- XP Embedded OS : SP2
- MS Remote Desktop Protocol Client
- ICA Citrix Client
- Unix emulation Suite client
- LPD : Printing daemon - independent application
- XLManage Agent : Client Control Software
- Internet Explorer : Web browser
- Media Player : Windows Media Player
- Acrobat reader
- JVM : Java
- VNC Viewer

Features :

- Wireless Support : VIA Compatible Fast Ethernet Adapter
- Smart Card Support : External USB SmartCard - SCR335 Model only
- Different Desktop / Kiosk modes
- Keyboard : Supports upto 20 different languages
- USB : Auto detection of usb plug and play devices
- Printer : Thinprint, ghostscript, etc are supported

Power

- Full Range 65W AC adapter - AC input 100~240V, 47~63Hz, DC output 20V, 3.25A

- Removable 6-cell Smart Li-ion battery pack, 4000/4400mAh

Regulatory Compliance

- TUV ■ cULus ■ C-TICK ■ VCI ■ CE ■ FCC

Warranty

One-year limited warranty



VXL Instruments Limited

Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines) Fax: +91 80 28520095 E-mail: sales@vxl.net Web: www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55 Fax: +44 (0) 16 17 75 48 66 E-mail: peter.best@vxl.net

VXL Presence:

France

Tel. : +33 (0) 1 42 17 00 03

E-mail: pjaspard@vxl.net

Germany

Tel. : +49 (0) 8761 1093

E-mail: gerdb@vxl.net

United States

Tel. : +1 713 589 3273

E-mail: sales@vxl.net