



## ITONA TL 3733

Networking Ideas  
..... Thin Solutions

# Thin Client



Itona TL is available with a variety of operating systems (Gio Linux and Microsoft Windows XP Embedded) so it connects easily to a wide range of servers and networks. With integrated 54Mbps wireless LAN as well as a 56K/V.92 modem and 10/100/1000 Ethernet, Itona TL delivers the security and central manageability of thin client computing - in a package that's as portable as it is stylish.

Itona TL gives you all the advantages of thin client computing - in a light, powerful laptop. Thin client computing, to go.



Itona TL

### About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide - with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters is in Bangalore, India.

### Fully featured

With an extensive range of ports (USB x3, audio, headphone, 10/100/1000 Ethernet, wireless LAN, VGA out and optional PCMCIA support), 32-bit graphics display and a removable battery, Itona TL has got pretty much everything you need. If you want more, you'll be pleased to hear that RAM can be upgraded to 2 GB - and Flash memory to 1 GB.

### Secure mobile computing

Central data storage, remote management software, BIOS password protection and a Kensington lock deliver workstation-class security - in a mobile device.

### Choice. Choice. And choice.

Itona comes in a range of configurations, so you can be sure that there's an ideal Itona for your network.

### Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

# ITONA TL 3733

## Thin Client



### Modular Terminal

Based on Linux 3.6

#### Standard Client Software:

Flash: 64MB (ATA Flash Drive 2.5") for GIO linux; RAM: 256 MB SO-DIMM DDR333/400MHz, Memory Expandable upto 1GB

### Hardware

**Processor :** VIA C7-M Processor 754 ( 1.50GHz )

#### Input/Output/Peripheral Support :

- 3 USB 2.0 ports
- 1x External CRT monitor output
- 1x Headphone jack
- 1x Microphone jack
- 1x S/PDIF output jack
- 1x RJ-45 port for LAN
- 1x RJ-11 port for Modem (functional option)
- 1x Line-in jack
- 1x DC-In jack
- A4 size keyboard, Multi-Language support, Winkey Keyboard
- Built-in Touchpad with scrolling function
- One Type-II PCMCIA CardBus PC Card Slot.
- Embedded 4 in 1 Card Reader.
- Optional PCMCIA support

#### Networking

- 10/100BASE-TX Fast Ethernet on board
- (Option) 802.11g MiniPCI Wireless LAN

#### Display Support

- 15" XGA + TFT
- High resolution 1024 x 768 with 32 bit
- Dual monitor display support

#### Audio

- AC'97 2.2 Compliant Interface
- 3D stereo enhanced sound system
- Virtual 6-channel audio output
- Sound-Blaster PROTM Compatible
- S/PDIF Digital output (5.1 CH)
- 1x Built-in Microphone
- 2x Built-in Speakers

#### Physical Characteristics

- Height : 1.3 Inches ( 33mm.)
- Depth : 10.9 inches ( 276mm)
- Desktop type Only
- Width : 13.1 inches (325mm)
- Shipping Weight : 2.5Kg with 6 cells

#### Temperature Range :

- 5 dec - 35 dec

#### Security :

- Security ( Kensington R Type ) Lock Slot, BIOS Password

### Software

#### Firmware Features :

- Linux 3.6
- MS Remote Desktop Protocol Client
- ICA Citrix Client
- Mozilla Fire Fox browser : Web Browser with XPDF for viewing pdf files
- Dial up ADSL
- Dial up ISDN
- PPTP : VPN
- REXEC : Display locally an application
- running remotely on unix/linux servers
- Unix emulation Suite client
- Connects to Tarantella Enterprise server
- X11 XDMCP protocol : Allows to connect to XDM servers
- SSH - Secure shell : utility to connect unix servers
- VNC Server : Connection for VNC viewing

#### Features :

- Different Desktop / Kiosk modes
- Keyboard : Supports upto 20 different languages
- USB : Auto detection of usb plug and play devices
- Printer : Thinprint, ghostscript, etc are supported
- Script Update : Clients can be automatically configured from dhcp scripts
- SMB / NFS : Mounting for accessing different folders over the network

#### Power

- Full Range 65W AC adapter - AC input 100~240V, 47~63Hz, DC output 20V, 3.25A
- Removable 6-cell Smart Li-ion battery pack, 4000/4400mAh

#### Regulatory Compliance

- TUV ■ cULus ■ C-TICK ■ VCI ■ CE ■ FCC

### Warranty

One-year limited warranty



### VXL Instruments Limited

Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines) Fax: +91 80 28520095 E-mail: sales@vxl.net Web: www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55 Fax: +44 (0) 16 17 75 48 66 E-mail: peter.best@vxl.net

#### VXL Presence:

##### France

Tel. : +33 (0) 1 42 17 00 03

E-mail: pjaspard@vxl.net

##### Germany

Tel. : +49 (0) 8761 1093

E-mail: gerdb@vxl.net

##### United States

Tel. : +1 713 589 3273

E-mail: sales@vxl.net