



ITONA TC 4621- XP

Thin Client

Networking Ideas

..... Thin Solutions



With a range of operating systems (Gio Linux, Microsoft Windows CE and Microsoft Windows XP Embedded) there's an Itona thin client for every organisation. Itona connects swiftly and easily to a wide range of servers and networks – and, once it's up and running, you'll enjoy the low cost of ownership and the near zero maintenance. It's the way enterprise computing should be.

Itona TC from VXL is thin client computing perfected. High specifications and low cost add up to a great value package that's secure, easy to manage and highly reliable.



Itona TC 4621

About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide – with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters is in Bangalore, India.

Fully featured

With an extensive range of ports (USB x4, PS/2 x2, serial x 2, parallel, audio, 10/100 Ethernet, optional : wireless LAN and smart card reader) Itona has really got connectivity covered. Add to that a 32-bit graphics controller and resolution support up to 1280x1024, it all adds up to one of the best specification thin clients around.

The ideal desktop client

Seen and not heard – that's Itona. That's because its fanless design ensures totally silent operation. And, of course, it is pleasing and compact – freeing up valuable desk space.

Choice. Choice. And choice.

Itona comes in a range of configurations, so you can be sure that there's an ideal Itona for your network.

Remote management included

Every Itona comes with the powerful XLmanage remote management software, Workgroup Edition, making central management a breeze.

ITONA TC 4621- XP

Thin Client



Modular Terminal

Based on the Microsoft Windows XP Embedded operating system

Standard Client Software:

Citrix ICA, Microsoft RDP, VNC, Internet Explorer, VOIP Software, Netscaler Software, "Go to Meeting" Software standard

Hardware

RAM : 512 MBDDR2 Upgradable upto 1GB

Flash : 512 MB Upgradable upto 4 GB

Processor : VIA C7, 1 GHz

Input/Output/Peripheral Support :

- 2 serial port
- 4 USB 2.0 ports (two on front, two on back)
- PS/2 Keyboard
- PS/2 Mouse
- VGA-type video output (DB-15)
- 1 Parallel Port (Female Connector D-Sub 25P)
- Built-in Kensington Security slot
- Internal USB Wireless LAN
- Internal USB Smartcard Reader (Optional)

Networking

- Autosensing, 10/100 Ethernet, RJ-45
- PXE boot
- Wake On Lan
- External wireless options

Display Support

- VESA monitor support, with Display Data Control (DDC) for automatic setting of resolution and refresh rate
- Maximum resolution and refresh rates (Hz)
 - 16 Bit Color : Up to 1600x1200 @ 70Hz
 - 32 Bit Color : Up to 1024x768 @ 60Hz; Up to 1280x1024 @ 85 Hz

Audio

- Line Out
- Mic
- Line In

Physical Characteristics

- Height : 8.89 inches (229mm)
- Depth : 9.0 inches (226mm)
- Optional : Wall Mounting bracket
- Width : 1.96 inches (50mm)
- Shipping Weight : Appx 2.5kg

Environmental

- Temperature Range :
 - Powered on : 32° to 104°F (0° to 40°C)
 - Powered off : -14° to 140°F (-10° to 60°C)
 - Convection cooling, fanless design
- Humidity :
 - 20% to 80% noncondensing

Software

Firmware Features :

- Microsoft Windows XPE
- Microsoft Internet Explorer 6.0 resident:
 - 1 HTML, JavaScript , XML, Active X, Sun JRE, MediaPlayer 6.4, Citrix Web Client
- RDP 6.0 resident
- Citrix ICA 10.xx resident

Server OS Compatibility/Support :

- Microsoft Windows 2000/2003 Server
- Citrix Winframe and MetaFrame
- Microsoft Windows NT Server 4.0 Terminal Server Edition

Security:

- EWF Manager, User registry restrictions

PLUG-INS:

- Adobe Acrobat Reader, Macromedia Flash wave and Shock wave

Set-Up & Configuration:

User interface :

- Boot from local Flash
- Windows XP user interface language:
 - U.S. English; French, German, Spanish optional
- Keyboard Language support:
 - U.S. English standard;
 - Support All other languages supported
- JAVA/ JVM, VNC Shadowing
- VPN, Customizable Thingerprint
- Smart Card Support, ELO Touch screen Support
- PPP / DIAL-UP- Networking
- USB Input Devices
- My ODBC Client Support

Protocol Support :

- TCP/IP, DNS, DHCP, PXE, RPL

Management

- Remote Management, configuration, and upgrades through XLManage software version 1.29 or later
- Wake terminal remotely (Wake-on-LAN)
- Terminal configuration (IP information, name, etc.)
- Reporting
- Remote screen shadowing of entire desktop (VNC)
- Asset management

Power

- Internal power supply
- Worldwide autosensing 100-240 VAC., 50/60 Hz, Less than 35 W (max)
- Average power usage: 16.0 Watts

Regulatory Compliance

- Ergonomics :
 - German EKH-TB 2000:2003
- Safety :
 - cTUVus, TUV-GS, TUV EMC
- RF Interference :
 - FCC Class B
 - CE
 - C-TICK
 - RoHS

Warranty

Three-years limited warranty



VXL Instruments Limited

Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines) Fax: +91 80 28520095 E-mail: sales@vxl.net Web: www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55 Fax: +44 (0) 16 17 75 48 66 E-mail: Derek.holloway@vxl.net

VXL Presence:

France

Tel. : +33 (0) 1 42 17 00 03
E-mail: pjaspard@vxl.net

Germany

Tel. : +49 (0) 8761 1093
E-mail: gerdb@vxl.net

United States

Tel. : +1 713 589 3273
E-mail: sales@vxl.net